

		GENERAL PURPOSE			REFRIGERATED			OPEN TOP			FLAT RACK	
		20GP	40GP	40HQ	20RF	20RH	40RH	20OT	20OH	40OT	20FR	40FR
EXTERNAL (M)	Length	6.05	12.19	12.19	6.05	6.05	12.19	6.05	6.05	12.19	6.05	12.19
	Width	2.43	2.43	2.43	2.43	2.43	2.43	2.43	2.43	2.43	2.43	2.43
	Height	2.59	2.59	2.89	2.59	2.89	2.89	2.59	2.89	2.59	2.59	2.59
INTERNAL (M)	Length	5.89	12.03	12.03	5.44	5.50	11.57	5.89	5.89	12.03	5.63	11.77
	Width	2.35	2.35	2.35	2.3	2.3	2.28	2.35	2.35	2.35	2.35	2.23
	Height	2.39	2.39	2.70	2.27	2.60	2.55	2.36	2.67	2.36	2.27	1.95
INTERNAL (CBM)	Capacity	33.2	67.8	76.4	28.3	32.2	67.6	32.64	39.25	66.96		
DOOR OPENING (M)	Height	2.28	2.28	2.58	2.26	2.56	2.56	2.28	2.58	2.28		
	Width	2.34	2.34	2.34	2.29	2.29	2.29	2.34	2.34	2.34		
RATING (T)	Max Gross	30.48	30.48	30.48	27.00	27.00	34.00	30.48	30.48	30.48	34.00	45.00
	Max Nett	28.3	26.74	26.63	23.62	23.75	29.28	28.08	27.96	26.64	31.00	40.00
	Tare	2.18	3.74	3.85	3.38	3.24	4.72	2.40	2.52	3.84	3.00	5.00

Disclaimer: The information provided hereon is a guide only and specifications may vary by container manufacturer, shipping line and/or material(s) used. If you are arranging movement of cargo which may be close to or exceed these specifications we suggest that you contact this office for clarification prior to making any booking.

All business is conducted by Acumation subject to it's Conditions of Carriage which are available at [www.acumation.com.au](http://www.acumation.com.au) or upon request.

© Acumation Pty. Ltd, 2011